



BATTERY PROTECTED BY 125 AMP FUSE WITHIN 12" OF BATTERY SOURCE

NOTES:
ELECTRICAL PANEL MUST BE MOUNTED IN A DRY LOCATION WITH AN AMBIENT TEMP UNDER 150° F AND PROPER VENTILATION.

PROPRIETARY & CONFIDENTIAL. UNPUBLISHED WORK COPYRIGHT PROTECTED PRO AIR, LLC. PRO AIR, LLC CLAIMS PROPRIETARY RIGHTS IN THE MATERIAL DISCLOSED HEREIN. NEITHER THIS DRAWING NOR ANY REPRODUCTION OR PORTION THEREOF MAY BE DISTRIBUTED OR USED TO MANUFACTURE ANYTHING SHOWN HEREIN WITHOUT PERMISSION IN WRITING FROM PROAIR, LLC.

REV. C

LET.	NO.	REVISION	BY	DATE	SIGNATURES	DATE	TITLE	USAGE	PART NO.	SCALE	SIZE	SHEET	OF
C	17-150	ADD DIODE FOR DEM A/C	CEB	6/15/17	DRAWN CEB	9/29/16	 2900 C.R. 6 W ELKHART, IN 46514	ACT - 933 HD, 923 HD	40 000 633	1" = 1" - 0"	A	1	1
B	17-144	EVAP AND COND UPDATE	CEB	6/7/17	CHECKED RAI	6/7/17							
A	16-126	RELEASED TO PRODUCTION	CEB	9/29/16									