



NOTES:
ELECTRICAL PANEL MUST BE MOUNTED IN A DRY LOCATION WITH AN AMBIENT TEMP UNDER 150° F AND PROPER VENTILATION.

BATTERY PROTECTED BY 125 AMP FUSE WITHIN 12" OF BATTERY SOURCE

PROPRIETARY & CONFIDENTIAL. UNPUBLISHED WORK COPYRIGHT PROTECTED PRO AIR, LLC. PRO AIR, LLC CLAIMS PROPRIETARY RIGHTS IN THE MATERIAL DISCLOSED HEREIN. NEITHER THIS DRAWING NOR ANY REPRODUCTION OR PORTION THEREOF MAY BE DISTRIBUTED OR USED TO MANUFACTURE ANYTHING SHOWN HEREIN WITHOUT PERMISSION IN WRITING FROM PROAIR, LLC.

REV. B

LET.	NO.	REVISION	BY	DATE	SIGNATURES	DATE	TITLE	USAGE	PART NO.	SCALE	SIZE	SHEET	OF
					DRAWN	CEB	9/29/16	SCHEMATIC, WIRE	40 000 634	1" = 1" - 0"	A	1	1
B	17-144	EVAP AND COND UPDATE	CEB	6/7/17	CHECKED	RAI	6/7/17						
A	16-126	RELEASED TO PRODUCTION	CEB	9/29/16				ACT - 933 DM, 923 DM					

